



Pacmasta[®]

Battery Powered Strapping Tool

Pacmasta ZP-93A/ZP-97A



Latest technology

- Brushless Motor provides long service life.
- Li-Ion battery, Bosch 30 minutes charger



Smart & Easy

- Pre-programmed touch panel
- Lightest model, easy removal of tool.
- Unique rear-end roller, soft mode



Powerful & Speedy

- Patented strap grippers design
- Single-handed operation



Safety

- Conforms to CE safety directive
- Battery complies with UN38.3 safety requirements.

Battery Powered Strapping Tool

Pacmasta ZP-93/97A



Standard Features



Latest technology

- Brushless Motor - patented single motor design provides extremely long service life.
- Bosch Li-Ion battery- 18V 4.0Ah (4000mAh) rechargeable battery with smart Charge Level Indicator (CLI).
- Bosch 30 minutes charger.



Powerful & Speedy

- Max. tension 400 KGS (4000N) - ZP97 heavy duty model.
- Max. tension 250 KGS (2500N) - ZP93 standard duty model.
- Patented new strap grippers design contributes to high tension ability and strap quality tolerance.
- Single-handed operation performs automatic tensioning, friction welding and cutting efficiently.



Smart & Easy

- Pre-programmed touch panel with digital signal to suit different operation needs.
- Lightest model in same class of tools approx. 3.5kg including battery relieves operation fatigue.
- Special tool retreating device ensures smooth and easy removal of tool.
- Unique rear-end roller design prevents scratches or damage on strapping objects.
- User self-adjustable strap width guides and self-changeable wearing parts.
- Optional hanger reduces operation fatigue.
- Soft mode tension available for slow and low tension when strapping light or fragile objects.



Safety

- Single-handed operation conforms to CE safety directive and meets RoHS requirements.
- Li-Ion battery complies with UN38.3 safety requirements.

Model	Battery Charger Voltage	Fits Poly Strap	Strap Width		Strap Thickness		Tension Range	Sealing Efficiency
			mm	inch	mm	inch		
ZP-93A	230V	PP	9-16	3/8-5/8	0.55 - 1.27	.022 - .05	10-250KG	85 5%
		PET	9-16	3/8-5/8	0.55 - 1.27	.022 - .05		
ZP-97A	230V	PP	16 & 19	5/8 & 3/4	0.75 - 1.27	.029 - .05	40-400KG	
		PET	16 & 19	5/8 & 3/4	0.65 - 1.27	.026 - .05		